

## **FILTER UNIT FT 001**

- Trailer mounted 40' Unit
- CW/ 2 - FSPN 2000/ 8 Sock Filter vessels
- Good for up to 22.5 BBLS per minute each
- Manifolder to use in Tandem or Individually
- Runs on 480 V / 3 Phase Power
- CW/ 70 KVA Generator
- 1-10 HP Monarch pre charged pump @ 14 BBLS/M
- 1-20 HP Monarch Unit Pump from Filter pods to storage @ 20 BBLS/I/I
- 2-5HP Monarch Transfer Pumps to move fluid anywhere on location @ 7 BBLS/M each
- Pumping section of unit is Class I Div. I Electrical System
- Unit is insulated & heated for winter operations
- Unit has exhaust fans to evacuate any steam or potential gas break out
- Unit has storage room for spare parts & dry sock storage
- Unit comes with tandem axle manifold trailer capable of suction & discharge into 7 tanks simultaneously & used to haul 300' of 4" hose & fittings.
- **OUR FILTER DISPOSAL WILL CONFORM TO ALL STATE, FEDERAL & OPERATING CO. REGULATIONS**

## **FILTER UNIT FT 002**

- Skid mounted 40' High Top Unit
- CW/ 3- FSPM 1100/ 6 Sock Filter vessels
- Good for up to 16.9 BBLS/M each designed to be able to filter water & oil simultaneously. Water side manifolded to use in Tandem or Individually
- Runs on 480 V/ 3 Phase Power
- CW/ 70 KVA Generator
- 1-10 HP Monarch pre charged pump" @ 14 BBLS/M
- 1-20 HP Monarch Pump from Filter pods to storage @ 20 BBLS/M
- 2-5HP Monarch Transfer Pumps to move fluid anywhere on location @ 7 BBLS/M each
- Pumping section of unit is Class I Div. I Electrical System
- Unit is insulated & heated for winter operations
- Unit has exhaust fans to evacuate any steam or potential gas break out
- Unit has storage room for spare parts 84 dry sock storage
- Unit comes with tandem axle manifold trailer capable of suction & discharge into 7 tanks simultaneously & used to haul 300' of 4" hose & fittings.
- **OUR FILTER DISPOSAL WILL CONFORM TO ALL STATE, FEDERAL & OPERATING CO. REGULATIONS**